

Picture	resilink )	
Model	Argus Series B340	
Video & Au- dio	Image Sensor	1/2.7"CMOS sensor
	Resolution	2880 x 1616 (5 megapixels) @15fps
	Video Compression	H.265
	Field of View	Horizontal: 105°
		Vertical: 55°
		Diagonal: 125°
	Infrared Night Vission	Up to 10 meters (33ft); LED: 8pcs/1.1w/850nm (Auto-switching with IR-cut filter)
	Color Night Vision	With spotlights: 2pcs/2w/6500k
	Frame Rate	Main stream: 10fps - 15fps (default: 15fps)
		Sub stream: 10fps - 15fps (default: 15fps)
	Code Rate	Main stream: 1024Kbps - 4096Kbps (default: 3072Kbps)
		Sub stream: 64Kbps - 672Kbps (default: 672Kbps)
	Audio	Two-way audio
Power Requirements	Battery	6000mAh rechargeable battery (Battery life varies based on settings, usage & temperature.)
Interface	Power Port	USB Type-C port
	SD Card Slot	Supports Max. 128GB microSD card
	Reset Button	YES
	Audio In/Out	Built-in microphone and speaker
Wi-Fi	Wireless Standard	IEEE 802.11 a/b/g/n
	Operating Fre- quency	2.4GHz/5GHz
	Wireless Security	WPA/WPA2



Picture	redink		
Model	Argus Series B340		
Software	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android	
	Protocols & Stand- ards	SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P	
	User Access	Max. 12 simultaneous streams (2 main & 10 sub streams)	
Other Fea- tures	Smart Alarm	PIR detection; person detection; vehicle detection; pet detection	
	PIR Detecting Dis- tance	Adjustable up to 10m (33ft)	
	PIR Detecting Angle	110° horizontal	
	Recording Modes	Triggered recording	
	Time Lapse	YES	
	Smart Home Compatibility	Google Assistant	
	Cloud Storage	Supports Reolink Cloud (available in selected countries)	
Working Environment	Operating Temper- ature	-10°C~+55°C (14°F~131°F)	
	Operating Humidi- ty	20% ~ 85%	
	Weatherproof	IP66	
Mechanical	Dimensions	191 x 75 x 75mm	
	Weight (Battery In- cluded)	431g	
Warranty	Limited Warranty	2-year limited warranty. For support, visit https:// support.reolink.com/hc/en-us/.	